

ROBUST BODY

Designed to work reliably in difficult conditions.

HIGH PERFORMANCE

Work wherever efficient and reliable ventilation is needed.

HIGH MOBILITY

Ergonomic handle combined with a low ventilator weight or a trolley makes moving the ventilator easy.

VENTILATORS

INELCO INDUSTRIAL VENTILATORS

INELCO ventilators keeps you cool







IAV-32/2S

wide air stream / high efficiency / 2 fan speed / adjustable air flow direction / trolley for easy transport / high mobility / powder coated durable body

IAV-24/2S

wide air stream / high efficiency / 2 fan speed / adjustable air flow direction / trolley for easy transport / compact dimensions / high mobility / powder coated durable body

TECHNICAL DATA	IAV-32/25 88041111	IAV-24/25 88041104
Maximum air flow [m³/h]	11400	8400
Power supply [V] / Frequency [Hz]	230V/50Hz	230V/50Hz
Max. energy consumption [W]	400	330
Fan type	axial	axial
Maximum fan speed [rpm]	960	1120
Fan speed levels	2	2
Fan diameter [mm]	800	600
Static [Pa]		80
Flexible tube ready	no	no
Air outlet diameter [mm]	810	680
IP protection class	44	54
Product size (LxWxH) [mm]	400x900x940	775x380x780
Net weight [kg]	36	23,24





IAV-20/3S

wide air stream / high efficiency / 3 fan speed / adjustable air flow direction / high mobility / powder coated durable body



narrow air stream / high efficiency / 1 fan speed / works well with flexible air ducts / compact dimensions / high mobility / powder coated durable body



TECHNICAL DATA	IAV-20/35 88041106	IAV-12/15 88041103
Maximum air flow [m³/h]	7200	3900
Power supply [V] / Frequency [Hz]	230V/50Hz	230V/50Hz
Max. energy consumption [W]	140	500
Fan type	axial	axial
Maximum fan speed [rpm]	1400	2800
Fan speed levels	3	1
Fan diameter [mm]	490	300
Static [Pa]		385
Flexible tube ready	no	yes
Air outlet diameter [mm]	530	330
IP protection class	44	54
Product size (LxWxH) [mm]	230x686x660	378x380x445
Net weight [kg]	10,37	15,33